

ANDEROL PRODUCT DATA SHEET

ANDEROL 86 EP-2 GREASE

CALCIUM SULFONATE COMPLEX GREASE NLGI-2

GENERAL INFORMATION

ANDEROL 86 EP-2 is an over-based Calcium Sulfonate based grease with exceptional load carrying ability, excellent mechanical stability and good resistance to oxidation and corrosion. ANDEROL 86 EP-2 equals or outperforms other premium greases in high-speed applications.

TYPICAL PROPERTIES

PROPERTY	TEST METHOD	ANDEROL 86 EP-2
Thickener		Ca-Sulfonate
Colour		Brown
Type of Base Oil		Mineral
Operating temperature for long-term lubrication		-20 to +160 °C
Short time admissible temperature peak value		+200 °C
Dropping Point	DIN ISO 2176	318 °C
Worked Penetration	DIN ISO 2137	265 to 295 0.1mm
Base Oil Viscosity at 40 °C	DIN 51.562	Approx. 135 mm ² /s
4-ball weld load	ASTM D-2596	5000 N
Water Washout at 80 °C	ASTM D-1264	0.5% removed
Bearing Life performance, 1000 rpm, 160 °C	ASTM D-3527	100 hours
Low Temperature Torque at -40 °C	ASTM D-4693	12.0 Nm
Designation	DIN 51.502	KP 2 U-40

ANDEROL 86 EP-2

For more information please refer to the relevant Material Safety Data Sheet accompanying each product.

®ANDEROL is a reg. trademark of ANDEROL COMPANY.

This information is furnished without warranty, representation, inducement, or license of any kind, except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL to be accurate. ANDEROL does not assume any legal responsibility for use of reliance upon it. Only chemists or chemically qualified lab technicians should carry out tests. Before using any chemical, read its label and Material Safety Data Sheet.

APPLICATIONS / ADVANTAGES

- Superior mechanical stability, particularly in the presence of heat and water
- Formulated to resist separation under centrifugal forces
- Excellent rust prevention properties
- Excellent load carrying ability and wear protection
- Excellent resistance to water washout and spray-off
- Suitable grease for high speed bearings
- Suitable for automotive and truck wheel bearings and chassis components
- Excellent Electric Motor bearing Grease
- Heavy duty industrial applications, e.g. Steel Mills

REGISTRATIONS / APPROVAL

Exceeds the requirements for NLGI GC/LB certification for use in automotive and truck wheel bearings and chassis components.


HANDLING AND STORAGE

ANDEROL Lubricants generally present little hazard in normal handling if ordinary care is exercised. If spilled, cover with inert, absorbent material and remove. Flush the area with water.

Although ANDEROL Lubricants are not highly flammable, they will burn and should be kept away from open flames. In case of fire, use water spray, foam, carbon dioxide, or dry chemical.

ANDEROL Lubricants should be stored preferably in protected locations to prevent contamination. Do not re-use drums; flush and send to reconditioner.

Edition 22-08/2008



ANDEROL[®]
Specialty Lubricants

ANDEROL EMEA
Punterweg 21a
6222 NW Maastricht
The Netherlands
Tel: +31-(0)43 352 4190
Fax: +31-(0)43 352 4199
E-mail: info@anderol-europe.nl